

# ISEKI TH Series SPECIFICATIONS

## TH4365

### MODEL

Drive 4WD

### ENGINE SPECIFICATION

Engine Iseki E3CG  
 No. Cylinders / cc 3 / 1647  
 Engine Power kW/hp 27/36  
 @ rated speed 2600  
 Speed control manual pedal & cruise control

### PTO

PTO kW / hp 21 / 28  
 Type Independent  
 Speeds Rear 540 / 1000  
 Mid PTO 2000@2500  
 Configuration rear/mid 6 spline / 15 spline

### TRANSMISSION

Type Hydrostatic  
 Speeds Fwd/Rev 3 / 3  
 Speed Range Std/Max F : 0 - 28.6 R : 0 - 21.7

### HYDRAULIC SYSTEM

Description Open Centre  
 Pump Type Gear  
 Max l/min (Main pump) 32  
 Remote Outlets Std/Max 2F 0R / 2F 2R

### 3 POINT LINKAGE

Type Cat I  
 Control Position  
 Lift - kg@610mm 730  
 Lift - kg@BE 1100

### BRAKES & STEERING

Brake Type Wet disc  
 Steering Type Hydrostatic

### AXLE CAPACITY

Rear Axle 1100kg  
 Front Axle 900kg

### TYRE EQUIPMENT - AG

Standard Front 6.00 - 14  
 Standard Rear 12.4 - 16

### DIMENSION/WEIGHTS

Minimum Width 1430mm  
 Height 2455mm  
 Wheel base 1695mm  
 Ground Clearance 220mm  
 Dry Shipping Weight 1220kg

### CAPACITIES

Fuel 35 litres  
 Transmission 34 litres  
 Engine crankcase 5.4 litres



Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.



**FREECALL: 1800 802 914**  
[www.agco.com.au](http://www.agco.com.au)



**smart, reliable** created with you in mind  
[www.iseki.com.au](http://www.iseki.com.au)



  
**ISEKI**

**TH Range Compact Tractors** All torque. All Action.

**36hp**

# ISEKI TH RANGE FEATURES



## POWERFUL ENGINE

Now boasting a bigger 36hp Iseki engine, delivering plenty of power at a low 2600rpm. Efficient and powerful. What you expect from an Iseki engine.



## NEW DESIGN

Rounded bonnet gives a modern look and has improved visibility for front-end loader application.



## ERGONOMIC OPERATOR AREA

An iso mounted platform reduces noise and vibration. A Deluxe seat is standard and controls are located on the fenders for more room and better control



## SERVICEABILITY

Easy access to the whole engine and daily check points easy to reach.



## IMPLEMENT CONTROL

large linkage and hydraulic capacity, a 540/1000 PTO and extendable drawbar is suitable to a large range of implements.



## PTO

The independent PTO with 2 speed modulation control for slow and smooth engagement. 540 and 1000 speed rear and a mid PTO as standard.



## HYDROSTATIC TRANSMISSION

Three range hydrostatic transmission give you more options and more working ranges. • Easy to use side by side forward and reverse pedals make directional changes smooth. • 4 wheel drive and differential lock for exceptional traction in all conditions.



## VERSATILE

AG or Turf tyres. Front end loader or 60 inch mower, the Iseki TH4365 is designed to take on a multitude of tasks.



# THE NEXT GENERATION

Iseki's determination to strive for perfection in the compact tractor sector is reflected in the next generation TH Series.

The impressive new tractor range boasts more power and better features befitting the most astute owner who demands nothing short of top performance, comfort and value in a compact tractor.

Clever, sleek new design and smart engineering combine with proven features to produce the new benchmark in compact tractors – the TH4365.

Whether it's a high performing professional mower to tackle the big jobs or a premium compact tractor, you can count on Iseki to deliver time and time again.

Formed in 1926, Iseki has been designing, manufacturing and supplying tractors worldwide for over 80 years and with over 30 years experience in the Australian market, Iseki is the brand you can trust.



Built to impress. The Iseki difference.